


SINGLE USE MANIFOLD CONNECTIONS



Single use AdvantaFlex manifolds are manufactured by molding straight sections of tubing or hose with connectors such as T's, Y's, and Tri-Clamps®. Molded connectors provide a seamless transition for a continuous, unrestricted, leak-proof flow by eliminating barbed fittings. AdvantaFlex manifolds are custom made to your specifications and available with **validated sterility assurance** of 10⁻⁶ per ISO 11137 method VDmax. Choose from the connection options listed here or suggest your own.



TPE
www.advantapure.com

Y Connector

Size range: .188" I.D. x .375" O.D.
(4.78mm I.D. x 9.53mm O.D.)
to: .500" I.D. x .750" O.D.
(12.70mm I.D. x 19.05mm O.D.)



T Connector

Size range: .125" I.D. x .250" O.D.
(3.18mm I.D. x 6.35mm O.D.)
to: .500" I.D. x .750" O.D.
(12.70mm I.D. x 19.05mm O.D.)



Cross

Size range: .125" I.D. x .250" O.D.
(3.18mm I.D. x 6.35mm O.D.)
to: .500" I.D. x .750" O.D.
(12.70mm I.D. x 19.05mm O.D.)



SINGLE USE MANIFOLD CONNECTIONS

Reducer Connector

Size range: .125" I.D. x .250" O.D.
(3.18mm I.D. x 6.35mm O.D.)
to: .750" I.D. x 1" O.D.
(19.05mm I.D. x 25.40mm O.D.)



Various size combinations within this range are available; call for details.

Tri-Clamp®

Size range: .375" I.D. x .625" O.D.
(9.53mm I.D. x 15.88mm O.D.)
to: .750" I.D. x 1" O.D.
(19.05mm I.D. x 25.40mm O.D.)



Available with polysulfone or stainless steel backing cups.

Other sizes in development

Mini Tri-Clamp®

Size range: .188" I.D. x .375" O.D.
(4.78mm I.D. x 9.53mm O.D.)
to: .375" I.D. x .625" O.D.
(9.53mm I.D. x 15.88mm O.D.)



Most sizes available with polysulfone or stainless steel backing cups; some larger sizes available with stainless steel only.

Many size combinations are available, and other sizes are in development—talk with a representative for details.

Purity in Fluid Flow Systems®



Made in U.S.A.

Address: NewAge Industries AdvantaPure®
145 James Way
Southampton, PA 18966 U.S.A.



DISTRIBUTED BY:

Toll Free Phone: **888-755-4370**
Phone: **215-526-2151**
Toll Free Fax: **888-258-4293**
Fax: **215-526-2167**
Web Site: **www.advantapure.com**
E-mail: **sales@advantapure.com**

©2017 NewAge® Industries, Inc. Specifications are subject to change without notice. AdvantaPure products are produced by NewAge® Industries, Inc. NewAge Industries AdvantaPure®, Purity in Fluid Flow Systems®, NewAge®, and the "N" logo are trademarks of NewAge® Industries, Inc. Tri-Clamp® registered trademark of Alfa Laval Inc.



WARRANTY: NewAge Industries AdvantaPure products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries AdvantaPure products, item for item, which after examination by NewAge Industries AdvantaPure are deemed defective. NewAge Industries AdvantaPure specifically disclaims any other liability. The data supplied is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application.

NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term NewAge.