



AdvantaFlex Molded Tubing Ends work well in Single-Use applications by reducing operational costs and improving production efficiency. They're compatible with sterile tubing welders and available from stock in a variety of tubing sizes and lengths for your biopharma fluid transfer applications.



KEY FEATURES








- Available in four tubing sizes and three tubing lengths
- Validated sterility assurance of 10-6 via gamma irradiation per ISO 11137 method VDmax 25
- Certified animal derived component free
- Made from FDA-approved ingredients
- ISO Class 7 clean room manufactured
- Tubing is heat sealable, moldable and translucent for visual contact with the flow
- Custom sizes, lengths, and packaging available
- Documented quality control; lot traceable with identification on packaging
- AdvantaFlex has a Master File with the U.S. Food and Drug Administration (#28810)











AdvantaFlex® Molded Tubing Ends





SPECIFICATIONS

Product Number (in	I.D.	n m.) (i	Wall	(mm.)	(in.)	D. (mm.)	Standard Available Length (in.)
APAF-BP-02-04-11Y-xxGS	.125	3.18	.063	1.59	.250	6.35	24, 48, 72
APAF-BP-04-08-11Y-xxGS	.250	6.35	.125	3.18	.500	12.70	24, 48, 72
APAF-BP-06-10-11Y-xxGS	.375	9.52	.125	3.18	.625	15.88	24, 48, 72
APAF-BP-08-12-11Y-xxGS	.500	12.70	.125	3.18	.750	19.05	24, 48, 72

All Molded Tubing Ends come with a mini Tri-Clamp molded to one end and a plug in the other end. Sold by standard available lengths listed above. Insert length in product number when ordering. Example: 24 in. of .125 in. I.D. x .250 in. O.D. tubing is product number APAF-BP-02-04-11Y-24GS. Molded Tubing Ends are supplied double bagged in Tyvek® or similar polybags, gamma sterilized and bulk packed. Custom sizes and lengths are available; contact your AdvantaPure Sales Representative for details.

AdvantaFlex tubing is flexible, translucent, sterilizable, moldable, weldable and heat sealable. Its unique properties help it outperform similar tubing in peristaltic pumps. Contact your AdvantaPure sales representative for more information or visit www.advantapure.com/advantaflex.htm.



Purity in Fluid Flow Systems®



Address: NewAge Industries AdvantaPure®

145 James Way

Southampton, PA 18966 U.S.A.

Advanta PÜRE®



 Toll Free Phone:
 888-755-4370

 Phone:
 215-526-2151

 Toll Free Fax:
 888-258-4293

 Fax:
 215-526-2167

Web Site: www.advantapure.com
E-mail: sales@advantapure.com

©2017 NewAge® Industries, Inc. Specifications are subject to change without notice. AdvantaPure products are produced by NewAge® Industries, Inc. AdvantaFlex®, Purity in Fluid Flow Systems®, NewAge Industries AdvantaPure®, NewAge®, and the "N" logo are registered trademarks of NewAge® Industries, Inc. Tri-Clamp® reg. TM Alfa Laval Inc. Tyvek® reg. TM Dupont.



